



EUROstor ES-8700 DSS V6 systems combine high performing hardware RAID 6 technology with Open-E's DSS V6 storage virtualization solution that gives you best flexibility in delivering storage capacity to different physical servers as well as virtual machines.

open-e Based on SATA or SAS drives, RAID sets defined on a hardware RAID controller can be assigned to volume pools. These can be easily expanded when more capacity is needed, just by adding new disks to the RAID.

Scheduled snapshots of iSCSI-Volumes and NAS-Shares can easily be mounted directly to a different server, making the backup / restore operations easy and independent from backup windows and allowing a simple and quick reconstruction of deleted data.

Dynamically scalable volumes within these pools avoid expensive unused resources. Additional capacity can be added just in time.

One of the core features of DSS V6 is the iSCSI-Failover capability, which is designed to meet the highest availability requirements. The data on the primary node is synchronously replicated to the secondary node, which will automatically take over once the primary node fails.

ES-8700 RAID powered by Open-E DSS V6 software can also be used as a NAS File server, also with asynchronous replication over LAN / WAN. With the optional Fibre Channel interface modules it can offer FC volumes for even higher traffic rates.

ES-8700 can also be offered with 2.5" disks drives, saving up to 60% of power costs per Terabyte.

ES-8700:

- Storage server running Open-E DSS V6
- iSCSI Failover capability
- RAID 0, 1, 5, 6, 10, 50, 60, hot spare
- snapshots of single RAID Volumes and NAS-Shares
- volume expansion
- 4 x 1 Gbit Ethernet interfaces optional more, also 10 Gbit
- iSCSI connection to Windows / Linux / Unix systems
- CHAP and IP masking on volume level
- redundant PSU
- easy management over web browser

8 - 24 bay systems:

- 1 - 4 U, 19" rackmountable, 2.5" or 3.5" disks
- 8 - 36 SAS or SATA disks per box, also mixed
- SAS: up to 600 GB each max. 21,6 TB per box (2.5" up to 900 GB 10K)
- SATA up to 108 TB per box with 3 TB disks
- optional 6 Gbit SAS expansion (total up to 128 disks)

Service:

- **3 years warranty**
- **free support via telephone or email**
- **optional: 3 years Express Exchange Service**
- **optional: 3 years On Site Service**

model	disks	rackmount size	size WxHxH	PSU
ES-8708xDSS	8	2 U	437x89x648	2x 700 Watt redundant
ES-8716xDSS	16	3 U	437x132x648	2x 800 Watt redundant
ES-8724xDSS25	24x 2.5"	2 U	437x89x597	2x 900 Watt redundant
ES-8724xDSS	24	4 U	437x178x660	2x 900 Watt redundant
ES-8736xDSS	36	4 U	437x178x699	2x 1400 Watt redundant

specifications	
disk interface	SAS or SATA-II (also mixed)
system architecture E3 series ES-87xxSDSS	<ul style="list-style-type: none"> Intel E3 processor on Sandy Bridge Board 16 GB RAM, optional up to 32 GB 4 Ethernet ports (1 Gbit), 1 IPMI port
system architecture E5 series ES-87xxDDSS	<ul style="list-style-type: none"> Intel E5 processor on Sandy Bridge Board , opt. dual processor 16 GB RAM, optional up to 768 GB 4 Ethernet ports (1 Gbit), 1 IPMI port
RAID controller features	<ul style="list-style-type: none"> RAID level 0, 1, 0+1, 3, 5, 6, JBOD multiple RAID selection online RAID level / stripe size modification online capacity expansion with RAID level migration direct availability of capacity – background initialization hot-spare disks automatic disk integration and automatic rebuild optional battery backup unit, up to 72 h
iSCSI features	<ul style="list-style-type: none"> Open-E DSS V6 software hardware and software iSCSI initiator support synchronous replication over LAN (2 systems required) iSCSI automatic failover (2 systems required) masking based on IP addresses CHAP user management MPIO support snapshots on volume level flexible volume expansion
NAS features	<ul style="list-style-type: none"> CIFS, NFS, FTP/FTPS, AppleTalk AD, LDAP backup agents (Veritas, EMC Dantz, CA BrightStor), licenses not included antivirus (server shares scanning) snapshots on volume level NAS volume replication synchronous / asynchronous (2 systems required) optional automatic NFS failover (2 systems required)
optional in E5 series	<ul style="list-style-type: none"> 10 Gbit iSCSI ports 8 Gbit FC ports for FC volumes
monitoring / management	<ul style="list-style-type: none"> integrated web based RAID and virtualization manager email notification hardware management and remote console over IPMI module
operating system support	OS independent (iSCSI hardware or software initiator required)
electrical	110-230 V AC, 50-60 Hz
temperature	operating: 5 – 35° C, non-operating: -40° – +60° C